



IAP6018E

Next-generation Wi-Fi 6 (802.11ax) Indoor Dual-band Wireless Access Point

Product Introduction

IAP6018E is a next-generation Wi-Fi 6 dual-band indoor access point and designed to meet rapidly rising demand for high capacity and bandwidth in indoor applications. Compliant with IEEE 802.11a/b/g/n/ac/ax standards, IAP6018E supports technologies such as OFDMA, MU-MIMO, TWT, and BSS coloring, providing a maximum bandwidth of 1.775 Gbps. IAP6018E supports standalone mode, AC management mode, and cloud management mode. IAP6018E delivers outstanding performance even in dense indoor deployment scenarios such as schools, hotels, stations, and airports.

Product Feature

High-performance Wi-Fi 6 access point

- Complies with Wi-Fi 6 (IEEE 802.11ax) standards
- Supports MU-MIMO and OFDMA to improve the user's Internet experience.
- Supports BSS Coloring mechanism.
- Provides up to 1.775 Gbps bandwidth (1.2 Gbps in the 5GHz band and 0.575 Gbps in the 2.4GHz band).
- Built-in Bluetooth enables Bluetooth serial port operation and precise positioning.

Robust security

- Supports WPA3 for multi-password authentication and encryption.
- Supports MAC authentication, 802.1X authentication, Web authentication, and transparent authentication
- Supports WPA3 256-bit encryption.
- Supports VPN tunnel technologies such as IPSEC, SoftGRE, and CAPWAP.
- Supports WLAN DOS attack detection and protection, as well as suppression of wireless broadcast messages.
- Supports terminal isolation based on SSIDs, APs, and VLANs.

Intelligent Wi-Fi access point

- Works with the O&M platform to serve as a local Portal gateway, capable of managing 1 to 16 conventional APs.
- Enables local Portal authentication and customized Portal advertisement push on the web page.
- Provides various local data collection and statistical analysis services.
- Supports end-user network behavior management, recognition of mainstream domestic apps, and network behavior management and control based on SSID.
- Provides a USB 2.0 charging port to extend USB local storage (supporting FAT32 file format) and IoT modules (such as RFID).

Smart Link connectivity management

- Actively monitors the link state with the access controller (AC) or gateway.
- Maintains existing terminal sessions and establishes new sessions when the AC is down.

Energy saving

- Power consumption is lower than 18W (excluding USB power consumption).
- Allows users to configure a timed shutdown policy for radio modules.

Effortless deployment and simplified O&M

- Supports PoE+ (802.3at) and local power options.
- Offers ceiling or wall-mounted installation options.
- Facilitates remote management via Telnet or SSH and automatic configuration retrieval from the cloud platform.
- Enables intelligent, visualized, and remote O&M, cloud diagnosis, fault alarms, and level-based and domain-based management.
- Supports centralized and local forward mode.

Feature-rich AP with centralized optimization and management

- Supports flexible operation modes including routing mode, Portal gateway mode, and bridge mode.
- Offers innovative AP functions, such as PPPoE, NAT, DHCP Server/Client, and wireless SSID and encryption settings.
- Supports up to 32 SSIDs and allows for setting parameters and security policies for each SSID individually.

Product Specification

Hardware specification	
Item	Parameter description
Port	<ul style="list-style-type: none"> 2 x 10/100/1000Base-T Ethernet ports 1 x USB 2.0
Bluetooth	<ul style="list-style-type: none"> 1 x Internal bluetooth 4.2
Reset button	<ul style="list-style-type: none"> 1 x Reset button
Power supply	<ul style="list-style-type: none"> 802.3at PoE+ DC, 12V/2A
Antenna	<ul style="list-style-type: none"> Internal antenna, 3 dBi gain
Operating frequency	<ul style="list-style-type: none"> 802.11a/n/ac/ax: 5.150~5.350 GHz; 5.470~5.725 GHz; 5.725~5.850 GHz 802.11b/g/n/ax: 2.40~2.4835 GHz
Spatial streams	<ul style="list-style-type: none"> 2.4G: 2 x 2 MU-MIMO 5G: 2 x 2 MU-MIMO
Max transmit power	<ul style="list-style-type: none"> 26dBm (23 dBm per chain)
Modulation technique	<ul style="list-style-type: none"> IEEE 802.11b: DSSS (DBPSK, QPSK, CCK) IEEE 802.11a/g: OFDM (BPSK, QPSK, 16-QAM, 64-QAM) IEEE 802.11n/ac: OFDM (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM) IEEE 802.11ax: OFDMA (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM)
Data rates	<ul style="list-style-type: none"> IEEE 802.11b: 11/5.5/2/1Mbps IEEE 802.11g: 54/48/36/24/18/12/9/6Mbps IEEE 802.11n: <ul style="list-style-type: none"> 20 MHz: 6.5 Mbps~144.4 Mbps 40 MHz: 13.5 Mbps~400 Mbps IEEE 802.11a: 54/48/36/24/18/12/9/6Mbps IEEE 802.11ac: <ul style="list-style-type: none"> 20 MHz: 6.5 Mbps~173.3 Mbps 40 MHz: 13.5 Mbps~400 Mbps 80 MHz: 29.3 Mbps~867 Mbps IEEE 802.11ax: <ul style="list-style-type: none"> 20MHz: 7.3 Mbps~286.8 Mbps 40MHz: 14.6 Mbps~573.6 Mbps 80MHz: 30.6 Mbps~1201 Mbps
Indicator	<ul style="list-style-type: none"> 1 x Power/status indicator 1 x 5G WLAN indicator 1 x 2.4G WLAN indicator 2 x Ethernet port indicators
Power consumption	<ul style="list-style-type: none"> 18W (excluding USB power consumption)
Dimensions	<ul style="list-style-type: none"> 7.87" x 7.87" x 1.77"(200 mm x 200 mm x 45 mm)
Weight	<ul style="list-style-type: none"> 1.76 lbs (0.80 kg)
Operating temperature	<ul style="list-style-type: none"> +14° F to +131° F (-10° C to +55° C)
Storage temperature	<ul style="list-style-type: none"> -40° F to +158° F (-40° C to +70° C)
Relative humidity	<ul style="list-style-type: none"> 5%~95% non-condensing

Software specification	
Item	Parameter description
Max SSIDs	<ul style="list-style-type: none"> 32
Max concurrent users	<ul style="list-style-type: none"> 256
802.11n/ac/ax	<ul style="list-style-type: none"> Automatic channel scanning 20 MHz/40 MHz/80 MHz channel bandwidth A-MPDU, A-MSDU Dynamic frequency selection (DFS) Transmit power control (TPC) Unscheduled automatic power save delivery (U-APSD)
802.11ax	<ul style="list-style-type: none"> OFDMA BSS Coloring TWT (Target Wake Time)
Wi-Fi security and authentication	<ul style="list-style-type: none"> WEP 64/128 WPA/WPA2-PSK-TKIP WPA/WPA2-PSK-CCMP WPA/WPA2-802.1X-TKIP WPA/WPA2-802.1X-CCMP WPA/WPA2-PPSK WPA3-ASE, WPA2/WPA3, WPA3-802.1X WAPI-PSK/CA MAC, Portal, Transparent Authentication and Dot1x Authentication (EAP-TLS, EAP-TTLS, EAP-PEAP, EAP-SIM/AKA, EAP-FAST)
Local AP functions	<ul style="list-style-type: none"> PPPoE Client, NAT, DHCP Server, DHCP Client Configuration of local SSID, encryption, and shared keys
QoS	<ul style="list-style-type: none"> Rate limitation based on STAs, SSIDs, and APs Maximum concurrent user limitation based on SSIDs Radius bandwidth property delivery voice QoS
Management	<ul style="list-style-type: none"> Network management and control via O&M platform or APP Network management via local CLI or local WebUI Network management via Telnet or SSH Upgrade through CAPWAP or FTP NTP, SYSLOG
Note:	<ul style="list-style-type: none"> Specifications are subject to change. Actual operating frequency varies according to the regulations of different countries and regions. Actual transmit power varies according to the regulations of different countries and regions. Actual number of concurrent users varies according to the application environment and other factors.